REQUEST FOR QUOTATION PROCUREMENT OF ICT EQUIPMENT RFQ N_571-KGZ_21

Date: June 14, 2021

Dear Sir / Madam,

You are kindly requested to submit your quotation for ICT Equipment in Kyrgyzstan as described in Annex B.

We also request that your Quotation is submitted using the format specifically detailed in Annex C.

Quotations submitted by email must be limited to a maximum of **10MB**, **virus-free** and no more than two email transmissions. They must be free from any form of virus or corrupted contents, or the quotations shall be rejected.

Quotation shall be evaluated based on lowest priced Quotation meeting requirements as per the criteria set in Annex A, point q.

In the event of a discrepancy between the unit price and the total price (obtained by multiplying the unit price and quantity), the unit price shall prevail and the total price shall be corrected by IDLO. If the Bidder does not accept the final price based on IDLO's correction of errors, its Quotation will be rejected.

The Bidders shall not vary their prices for any reason after the deadline of the tender and while the Quotation is still valid. At the time of award of Contract, IDLO reserves the right to vary (increase or decrease) the quantity of goods services, by up to a maximum twenty-five per cent (25%) of the total offer, without any change in the unit price or other terms and conditions.

IDLO is not bound to accept any Quotation, nor award a Contract, nor be responsible for any costs associated with a Bidder's preparation and submission of a Quotation, regardless of the outcome or the manner of conducting the selection process.

IDLO encourages every prospective Supplier to avoid and prevent conflicts of interest, by disclosing to IDLO if you, or any of your affiliates or personnel, were involved in the preparation of the requirements, design, specifications, cost estimates, and other information used in this RFQ.

By submitting a Quotation in response to this information, Bidders are confirming acceptance of IDLO's General Terms and Conditions in full and Payment Policy of payment within 30 days after delivery of service on presentation of complete and correct invoice.

This Request for Quotation (RFQ) is comprised of:

Instruction to Bidders	Annex A
Technical Specifications	Annex B
Supplier's Quotation	Annex C
IDLO General Terms and Conditions for the Procurement of Goods or Services	Annex D
and IDLO Supplier Code of Conduct	



For any questions/clarifications related to this RFQ please contact IDLO on tenders@idlo.int and mention Clarifications RFQ N_571-KGZ_21 in the subject section of your email no later than 48 hours prior to the deadline for submission.

The Quote shall be addressed to IDLO on or before

Date: June 22, 2021

Time: 15:00 hours Rome local time.

Thank you and we look forward to receiving your quotation.

Sincerely yours, International Development Law Organization | IDLO Kyrgyzstan Country Office



Annex A Instructions to Bidders

a.	Description of requested Goods	See Annex B
b.	Deadline for Quotation	The Quote shall be addressed to IDLO on or before Date: June 22, 2021 Time: 15:00 hours Rome local time.
C.	General Terms and Conditions	Any bid submission will imply the unconditional acceptance of IDLO General Terms and Conditions for the Procurement of Goods and adherence to the Supplier Code of Conduct.
d.	Payment Terms	IDLO will conduct the payment within 30 days after satisfactory receipt of all goods and upon submission of the invoice by the Supplier.
e.	Conditions for Release of Payment	IDLO Acceptance of Goods Form based on full compliance with RFQ requirements
f.	Validity of Quotation starting from the Deadline of the Tender	In exceptional circumstances, IDLO may request the Bidder to extend the validity of the Quotation beyond what has been initially indicated in this RFQ. The Bidder shall then confirm the extension in writing, without any modification whatsoever on the Quotation.
g.	Quotations Submission	All quotations shall be submitted through the following e-mail address: tenders@idlo.int
h.	Partial Quotations	☐ Not permitted ☑ Permitted Bidders may submit a Quote for one or more Lots
i.	Place of Delivery	Goods shall be delivered to: 171 Junusalieva Street Bishkek Kyrgyzstan
j.	Delivery Terms	Incoterms Delivery Duty Paid (DDP) Goods will be delivered within 90 days after receipt of PO or contract from IDLO to Bishkek, Kyrgyzstan.
k.	Customs clearance, if needed, shall be done by:	□ IDLO ☑ Supplier □ N/A
I.	Currency of Quotation	Kyrgyz Soms Note: (Local Suppliers must comply with any applicable laws regarding doing business in other currencies)



m.	Value Added Tax on Price Quotation	☑ Must be inclusive of VAT and other applicable indirect taxes ☐ Must be exclusive of VAT and other applicable indirect taxes
n.	Preliminary Documents to be Submitted	 ☑ Annex C duly signed and stamped, and in accordance with the list of requirements in Annex B; ☑ Product Catalogues or Brochures (Product Data Sheets) attesting compliance with Technical Specifications as mentioned under Annex B; ☑ Provision of Serial Numbers at Time of Shipment to be included in Contract and to be counterchecked by IDLO at the time of Delivery: ☑ Quality Certificates for the Goods (ISO, etc.); ☑ Latest Business Registration Certificate; ☑ Latest Internal Revenue Certificate / Tax Clearance; ☑ Manufacturer's Authorization of the Company as a Sales Agent (if Supplier is not the manufacturer); ☑ Minimum two (2) Contracts/LPOs of similar value and nature in the past two (2) years as proof of experience with UN Agencies, INGOs, NGOs, or Foreign Embassies indicating contactable domain email references for verification ☑ Letters of Reference from at least two (2) clients indicating delivery of similar Goods in the past two (2) years with contactable
		domain email references for verification ☑ Relevant Company Profile
0.	Special Packing Requirement	⊠ N/A □ Yes
p.	After-sales services required, if applicable	 ☑ Warranty on Parts and Labour for minimum period of 1 year ☐ Technical Support ☐ Provision of Service Unit when pulled out for maintenance/ repair ☐ Others
q.	Evaluation Criteria	 Evaluation will be done according to the following order of priorities: Full submission of Preliminary Documents (as per Annex A, point n.) Technical responsiveness Comprehensiveness of after-sales services, as per Annex A, point p, if applicable. Earliest Delivery Date Lowest price
r.	Liquidated Damages	 □ N/A ☑ Yes - For late delivery of Goods, IDLO shall be entitled to claim liquidated damages from the Contractor in accordance with Article 23 of the General Terms and Conditions. Liquidated damages for inferior quality or non-conformance of specifications of Goods will be assessed on a case-by-case basis in accordance with the severity of the problem as determined solely by



IDLO. The application of this liquidated damages provision shall not
relieve the Contractor of its obligations or liabilities pursuant to this
Contract.



ANNEX B TECHNICAL SPECIFICATIONS

General Requirements

- 1. Equipment and consumables must ensure a consistently high quality of operation and be reliable.
- 2. Used, reconditioned, recycled, or modified in any way equipment or consumables are not allowed.
- 3. Equipment from leading manufacturers should be provided.
- 4. All proposed equipment characteristics must meet or exceed the minimum technical characteristics indicated in this technical specification.
- 5. Full warranty (factory warranty and maintenance servicing guarantee) for the supplied equipment and consumables must be valid for at least 12 months.
 - i. During the warranty period, the restoration of equipment operability at the Customer's site shall be within one working week.
 - ii. During the warranty period, if it is impossible to restore the functionality of the failed equipment (in a warranty case), it must be replaced with the same model or a similar counterpart (as agreed with the Customer) within 14 working days.
- 6. The equipment must be supplied with a full set of drivers for installed devices on electronic media.
- 7. Delivery at the request of the supplier or buyer can be carried out ahead of schedule.
- 8. All hardware must be designed for operation in the following conditions (GOST 2132-80 / for enclosed spaces/):
 - power supply parameters (220 V + 10 / -15%, 50 Hz +/- 1 Hz);
 - ambient temperature from + 10 ° C to + 32 ° C;
 - relative humidity from 40% to 80% at a temperature of 23 ° C. Life time of the equipment must be at least 5 years.



Specifications for Goods

Lots	Item Name	Specification	Unit measure	Quantity
Lot 1	Uninterruptible Power Supply for Personal Computer	 UPS type: Line-interactive Power capacity: 1200VA / 720W Input voltage: 220V Output voltage 220V +/-10% Input frequency: 45-65Hz Output frequency: 50/60 ± 0.5Hz Power cable length: 1.5 meters AVR operating range: 165-275V Number and type of output connectors: 3 x Schuko Mode switching time: 3 ms Output waveform: Step Sine wave Number and type of batteries: 12V / 7.5Ah x 2 Battery charge time: 6-8 hours Front panel: LED indicators Interface for communication with a PC USB (Smart technology) Auto turn on Silent mode Telephone line protection Battery deep discharge protection 	UNIT	15
Lot 2	3 TB hard drive	 Short circuit and overload protection Size: at least 3,000 GB Digital storage buffer: at least 64 MB 4 KB Sector Support: yes Form factor: 3.5 " Rotational speed (RPM): not less than 7200 RPM Connection: SATA 6Gbit/s Max. interface speed: 600 MB /s 	UNIT	10
Lot 3	Video conferencing subsystem image display screen	 Screen diagonal: 43 "(108cm) Matrix type: LED IPS Screen resolution: 1920 x 1080 Full HD Viewing angle: 178° / 178° Acoustic system: two speakers Sound power: 20W The number of HDMI ports: not less than 2 Wall mountable VESA size: 200x200 Remote control 	UNIT	10



Lots	Item Name	Specification	Unit measure	Quantity
Lot 4	Network video recorder (NVR)	 Compression format: H.265/H.264/MPEG4 IP video input: 4 channels Incoming bandwidth: 40 Mbps Outgoing bandwidth: 80 Mbps Video / Audio outputs HDMI: 4K (3840×2160)/60Hz, 4K (3840×2160)/30Hz, 1920×1080/60Hz, 1600×1200/60Hz, 1280×1024/60Hz, 1280×720/60Hz, 1024×768/60Hz VGA: 1920x1080P/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz Audio output: 1-ch, RCA (Line, 1 KΩ) Recording resolution: 8MP/6MP/5MP/4MP/3MP/1080p/UXGA /720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF Interface type: 1 SATA up to 6TB External interfaces Dual audio streaming: 1-ch, RCA (2.0 Vp-p, 1kΩ) Network interface: 1 RJ-45 10 M/100 Mbps USB interface: 2 × USB 2.0 	UNIT	2
Lot 5	4 TB hard drive	 Size: 4 000 GB Digital storage buffer: 64 MB 4 KB Sector Support: yes Form factor: 3.5 " Purpose: for server / for video surveillance systems Rotational speed (RPM): 5,400 rpm Recording / read rate: 150/150 MB / s Connection: SATA 6Gbit / s Max. interface speed: 600 MB / s Operational shock resistance: 30 G Storage shock resistance: 250 G Operation noise level: 26 dB Idle noise level: 25dB Power consumption: 5.10 W 	UNIT	10



Lot 6	IP camera	 Matrix: 1/2.8" Progressive Scan CMOS Resolution: 2MP Sensitivity: 0.01 Lux @ (F1.2, AGC on), 0 Lux with IR Electronic shutter: 1/3 sec ~ 1 / 100,000 sec Lens: Motorized f = 2.8 - 12mm / F1.4 Viewing angle: 100 ° ~ 35 ° Lens mount: Φ14 Day / Night Mode: Mechanical IR Cut Filter with Auto Switching 3-axis adjustment: Panorama: 0 ° - 360 ° Tilt: 0 ° - 75 ° Rotation: 0° - 360° Video compression: H.264/MJPEG/H.264+ H.264 Profile: Main Profile Video bitrate: 32 Kb/s - 8 Mb/s Maximum resolution: 1920×1080 Main stream Max. frame frequency: 50Hz: 25fps (1920 × 1080, 1280 × 960, 1280 × 720) 60Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720) Additional stream Max. frame frequency: 50Hz: 25fps (704 × 576, 640 × 360, 352 × 288, 320 × 240) 60Hz: 30fps (704 × 480, 640 × 360, 352 × 240, 320 × 240) Image settings: Adjustment of brightness, contrast, saturation via client software or Web browser Day / Night Switch: Mechanical IR cut filter with auto switch Motion detection: Detection of: intrusion, defocus, motion. Dynamic analysis, tampering alert, network outage, IP address conflict, storage exceptions 	UNIT	10
		 Web browser Day / Night Switch: Mechanical IR cut filter with auto switch Motion detection: Detection of: intrusion, defocus, motion. Dynamic analysis, 		
		 address conflict, storage exceptions Network storage: micro SD / SDHC / SDXC, up to 128GB Protocols: TCP/IP, UDP, ICMP, HTTP, 		
		HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour Security: Password protection, watermark,		
		dual streamCompatibility: ONVIF, PSIA, CGI, ISAPI		



Lots	Item Name	Specification	Unit measure	Quantity
		 Alarm Triggered: Video Spoofing, Network Break, IP Address Conflict, HDD Full, HDD Errors Network interface: 1 RJ45 10M / 100M Ethernet Video input: 1 BNC Reset button: Yes Power supply: DC12B ± 25%/PoE (802.3af, class 3) Power consumption: 5.5W max. IR illumination: 30m Protection class: IP67, IK10 Working temperature: -30 ° C ~ + 60 ° C, humidity 95% or less (non-condensing) 	measure	
		Body material: Metal		
Lot 7	PoE switch	 Ethernet ports (Uplink): 2x10 / 100Base-T RJ-45 Ethernet ports (DownLink): 4x10 / 100Base-T PoE Network standards: IEEE802.3, IEEE802.3u, IEEE802.3X Max. bandwidth: 1.2 Gbps Packet Forwarding Rate: 0.8688Mbps Buffer memory: 768K MAC table size: 2K PoE protocols: 802.3af / at (PSE) PoE pinout: 1/2 (+) 3/6 (-) Power: DC 52V / 1.2A Power consumption: 63W 	UNIT	5
Lot 8	PC power supply	 Form Factor: ATX Power (nominal): not less than 500W Current on the +12 V line is not less than 14 A Current on the +5 V line is not less than 16 A Mains input voltage range: 100-240V 50 / 60Hz Availability of 4pin Molex connectors Active cooling system The package must include a mains power cable 	UNIT	30



Lots	Item Name	Specification	Unit measure	Quantity
Lot 9	Video capture card	 Interface: PCI Express x1 Gen 2 Input signal: HDMI *, 3.5mm audio Output: HDMI (pass-through), 3.5mm audio Maximum capture resolution: 1080p / 60 Bundled software Software compatibility: UVC / UAC compatible software such as XSplit or OBS 	UNIT	5



Personal Computer (Recording Station as a unit) Processor x86 Intel Core i7 (or equivalent), four physical cores, at least 3.5 GHz, cache at least 8 MB; Processor x86 Intel Core i7 (or equivalent), four physical cores, at least 3.5 GHz, cache at least 8 MB; Processor x86 Intel Core i7 (or equivalent), four physical cores, at least 3.5 GHz, cache at least 8 MB; Processor x86 Intel Core i7 (or equivalent), four physical cores, at least 3.5 GHz, cache at least 2 MB; Processor x86 Intel Core i7 (or equivalent), four physical cores, at least 2.5 GHz, ache at least 2 MB; Processor x86 Intel Core i7 (or equivalent), four physical cores, at least 2.5 GHz, ache at least 2 MB; Processor x86 Intel Core at least 2 MB;			The personal computer must meet the following		-
completeness System unit: Case with power supply, RACK form factor, size 19 ", power supply capacity at least 500 W, standard size power supply, at least 2 USB front panel connectors, headphones, microphone; Motherboard, with support for multi-core processors, 4 DIMM slots for DDR4 RAM modules, maximum system memory up to 64 GB; Compatible with DDR4 2666/2400/2133 MHz RAM modules; The number of USB 2.0 interfaces is at least 6 and the number USB 3.0 interfaces is at least 2, installed with D-Sub, HDMI video outputs, the integrated network controller must be of the Ethernet 10/100/1000 Mbps RJ 45 port type, expansion slots must meet the requirements for the functioning of the video capture, video recording and audio recording system; Percessor x86 Intel Core I7 (or equivalent), four physical cores, at least 3.5 GHz, cache at least 8 MB; The type of random access memory (RAM) must be at least 16 GB, and a two-channel operating mode must be organized. The storage drive must be in the form of at least two hard drives, each with a volume of at least 3000 GB, equipped with a SATA interface, with a spindle speed of at least 7200 rpm. Hard drives must be combined into a mirror array. SATA DVD-RW Drive; Monitor: Diagonal - 23.8 inches Aspect ratio - 16: 9 Resolution - not less than 1920 x 1080 Pixel size - no more than 0.278 mm			The personal computer must meet the following		
System unit:			· · · · · · · · · · · · · · · · · · ·		
Case with power supply, RACK form factor, size 19 ", power supply capacity at least 500 W, standard size power supply, at least 2 USB front panel connectors, headphones, microphone; Motherboard, with support for multi-core processors, 4 DIMM slots for DDR4 RAM modules, maximum system memory up to 64 GB; Compatible with DDR4 2666/2400/2133 MHz RAM modules; The number of USB 2.0 interfaces is at least 6 and the number USB 3.0 interfaces is at least 2, installed with D-Sub, HDMI video outputs, the integrated network controller must be of the Ethernet 10/100/1000 Mbps RJ 45 port type, expansion slots must meet the requirements for the functioning of the video capture, video recording and audio recording system; Processor x86 Intel Core i7 (or equivalent), four physical cores, at least 3.5 GHz, cache at least 8 MB; The type of random access memory (RAM) must be at least 16 GB, and at two-channel operating mode must be organized. The storage drive must be in the form of at least two hard drives, each with a volume of at least 3000 GB, equipped with a SATA interface, with a spindle speed of at least 7200 rpm. Hard drives must be combined into a mirror array. SATA DVD-RW Drive; Monitor: Diagonal - 23.8 inches Aspect ratio - 16:9 Resolution - not less than 1920 x 1080 Pixel size - no more than 0.278 mm					
size 19 ", power supply capacity at least 500 W, standard size power supply, at least 2 USB front panel connectors, headphones, microphone; • Motherboard, with support for multi-core processors, • 4 DIMM slots for DDR4 RAM modules, maximum system memory up to 64 GB; • Compatible with DDR4 2666/2400/2133 MHz RAM modules; • The number of USB 2.0 interfaces is at least 6 and the number USB 3.0 interfaces is at least 5 (in the faces is at least 2, installed with D-Sub, HDMI video outputs, the integrated network controller must be of the Ethernet 10/100/1000 Mbps RI 45 port type, expansion slots must meet the requirements for the functioning of the video capture, video recording and audio recording system; • Processor x86 Intel Core i7 (or equivalent), four physical cores, at least 3.5 GHz, cache at least 8 MB; • The type of random access memory (RAM) must be at least 10 DR4 2400 SDRAM, the total size of RAM must be at least 16 GB, and a two-channel operating mode must be organized. • The storage drive must be in the form of at least two hard drives, each with a volume of at least 3000 GB, equipped with a SATA interface, with a spindle speed of at least 7200 rpm. Hard drives must be combined into a mirror array. • SATA DVD-RW Drive; Monitor: • Diagonal - 23.8 inches • Aspect ratio - 16: 9 • Resolution - not less than 1920 x 1080 • Pixel size - no more than 0.278 mm			•		
Soo W, standard size power supply, at least 2 USB front panel connectors, headphones, microphone; Motherboard, with support for multi-core processors, 4 DIMM slots for DDR4 RAM modules, maximum system memory up to 64 GB; Compatible with DDR4 2666/2400/2133 MHz RAM modules; The number of USB 2.0 interfaces is at least 6 and the number USB 3.0 interfaces is at least 6 and the number USB 3.0 interfaces is at least 6 and the number USB 3.0 interfaces is at least 6 and the number USB 3.0 interfaces is at least 6 and the number USB 3.0 interfaces is at least 2, installed with D-Sub, HDMI video outputs, the integrated network controller must be of the Ethernet 10/100/1000 Mbps RJ 45 port type, expansion slots must meet the requirements for the functioning of the video capture, video recording and audio recording system; Processor x86 Intel Core i7 (or equivalent), four physical cores, at least 3.5 GHz, cache at least 8 MB; The type of random access memory (RAM) must be at least 10 GB, and a two-channel operating mode must be organized. The storage drive must be in the form of at least wohard drives, each with a volume of at least 3000 GB, equipped with a SATA interface, with a spindle speed of at least 7200 rpm. Hard drives must be combined into a mirror array. SATA DVD-RW Drive; Monitor: Diagonal - 23.8 inches Aspect ratio - 16: 9 Resolution - not less than 1920 x 1080 Pixel size - no more than 0.278 mm					
least 2 USB front panel connectors, headphones, microphone; Motherboard, with support for multi-core processors, 4 DIMM slots for DDR4 RAM modules, maximum system memory up to 64 GB; Compatible with DDR4 2666/2400/2133 MHz RAM modules; The number of USB 2.0 interfaces is at least 6 and the number USB 3.0 interfaces is at least 6 and the number USB 3.0 interfaces is at least 6 is at least 2, installed with D-Sub, HDMI video outputs, the integrated network controller must be of the Ethernet 10/100/1000 Mbps RJ 45 port type, expansion slots must meet the requirements for the functioning of the video capture, video recording and audio recording system; Processor x86 Intel Core i7 (or equivalent), four physical cores, at least 3.5 GHz, cache at least 8 MB; The type of random access memory (RAM) must be at least 16 GB, and a two-channel operating mode must be organized. The storage drive must be in the form of at least two hard drives, each with a volume of at least two hard drives, each with a volume of at least two hard drives must be combined into a mirror array. SATA DVD-RW Drive; Monitor: Diagonal - 23.8 inches Aspect ratio - 16: 9 Resolution - not less than 1920 x 1080 Pixel size - no more than 0.278 mm					
headphones, microphone; Motherboard, with support for multi-core processors, 4 DIMM slots for DDR4 RAM modules, maximum system memory up to 64 GB; Compatible with DDR4 2666/2400/2133 MHz RAM modules; The number of USB 2.0 interfaces is at least 6 and the number USB 3.0 interfaces is at least 2, installed with D-Sub, HDMI video outputs, the integrated network controller must be of the Ethernet 10/100/1000 Mbps RI 45 port type, expansion slots must meet the requirements for the functioning of the video capture, video recording and audio recording system; Processor x86 Intel Core i7 (or equivalent), four physical cores, at least 3.5 GHz, cache at least 8 MB; The type of random access memory (RAM) must be at least 16 GB, and a two-channel operating mode must be organized. The storage drive must be in the form of at least two hard drives, each with a volume of at least 3000 GB, equipped with a SATA interface, with a spindle speed of at least 7200 rpm. Hard drives must be combined into a mirror array. SATA DVD-RW Drive; Monitor: Diagonal - 23.8 inches Aspect ratio - 16: 9 Resolution - not less than 1920 x 1080 Pixel size - no more than 0.278 mm					
Personal Computer (Recording Station as a unit) Processor x86 Intel Core i7 (or equivalent), four physical cores, at least 3.5 GHz, cache at least 8 MB; The type of random access memory (RAM) must be at least 16 GB, and a two-channel operating mode must be organized. The storage drive must be in the form of at least two hard drives, each with a volume of at least 3000 GB, equipped with a SATA interface, with a spindle speed of at least 7200 rpm. Hard drives must be combined into a mirror array. SATA DVD-RW Drive; Monitor: Diagonal - 23.8 inches Aspect ratio - 16: 9 Resolution - not less than 1920 x 1080 Pixel size - no more than 0.278 mm					
Personal Computer (Recording Station as a unit) Personal Computer (Recording Station as a unit) Processor x86 Intel Core i7 (or equivalent), four physical cores, at least 16 GB, and a two-channel operating mode must be organized. The type of random access memory (RAM) must be at least 16 GB, and a two-channel operating mode must be of at least 10 GB, and a two-channel operating mode must be of at least 3000 GB, equipped with a SATA interface, with a spindle speed of at least 7200 rpm. Hard drives must be combined into a mirror array. SATA DVD-RW Drive; Monitor: Diagonal - 23.8 inches Aspect ratio - 16: 9 Resolution - not less than 1920 x 1080 Pixel size - no more than 0.278 mm			Motherboard, with support for multi-core		
maximum system memory up to 64 GB; Compatible with DDR4 2666/2400/2133 MHz RAM modules; The number of USB 2.0 interfaces is at least 6 and the number USB 3.0 interfaces is at least 2, installed with D-Sub, HDMI video outputs, the integrated network controller must be of the Ethernet 10/100/1000 Mbps RI 45 port type, expansion slots must meet the requirements for the functioning of the video capture, video recording and audio recording system; Processor x86 intel Core i7 (or equivalent), four physical cores, at least 3.5 GHz, cache at least 8 MB; The type of random access memory (RAM) must be at least 16 GB, and a two-channel operating mode must be organized. The storage drive must be in the form of at least two hard drives, each with a volume of at least 3000 GB, equipped with a SATA interface, with a spindle speed of at least 7200 rpm. Hard drives must be combined into a mirror array. SATA DVD-RW Drive; Monitor: Diagonal - 23.8 inches Aspect ratio - 16: 9 Resolution - not less than 1920 x 1080 Pixel size - no more than 0.278 mm			processors,		
Compatible with DDR4 2666/2400/2133 MHz RAM modules; The number of USB 2.0 interfaces is at least 6 and the number USB 3.0 interfaces is at least 2, installed with D-Sub, HDMI video outputs, the integrated network controller must be of the Ethernet 10/100/1000 Mbps RJ 45 port type, expansion slots must meet the requirements for the functioning of the video capture, video recording and audio recording system; Processor x86 Intel Core i7 (or equivalent), four physical cores, at least 3.5 GHz, cache at least 8 MB; The type of random access memory (RAM) must be at least 16 GB, and a two-channel operating mode must be organized. The storage drive must be in the form of at least two hard drives, each with a volume of at least 3000 GB, equipped with a SATA interface, with a spindle speed of at least 7200 rpm. Hard drives must be combined into a mirror array. SATA DVD-RW Drive; Monitor: Diagonal - 23.8 inches Aspect ratio - 16: 9 Resolution - not less than 1920 x 1080 Pixel size - no more than 0.278 mm			 4 DIMM slots for DDR4 RAM modules, 		
MHz RAM modules; The number of USB 2.0 interfaces is at least 6 and the number USB 3.0 interfaces is at least 6 and the number USB 3.0 interfaces is at least 2, installed with D-Sub, HDMI video outputs, the integrated network controller must be of the Ethernet 10/100/1000 Mbps RI 45 port type, expansion slots must meet the requirements for the functioning of the video capture, video recording and audio recording system; Processor x86 Intel Core i7 (or equivalent), four physical cores, at least 3.5 GHz, cache at least 8 MB; The type of random access memory (RAM) must be at least 16 GB, and a two-channel operating mode must be organized. The storage drive must be in the form of at least two hard drives, each with a volume of at least 3000 GB, equipped with a SATA interface, with a spindle speed of at least 7200 rpm. Hard drives must be combined into a mirror array. SATA DVD-RW Drive; Monitor: Diagonal - 23.8 inches Aspect ratio - 16: 9 Resolution - not less than 1920 x 1080 Pixel size - no more than 0.278 mm					
Personal Computer (Recording Station as a unit) Personal Computer (Recording System; Processor x86 Intel Core i7 (or equivalent), four physical cores, at least 3.5 GHz, cache at least 8 MB; The type of random access memory (RAM) must be at least 16 GB, and a two-channel operating mode must be organized. The storage drive must be in the form of at least two hard drives, each with a volume of at least 3000 GB, equipped with a SATA interface, with a spindle speed of at least 7200 rpm. Hard drives must be combined into a mirror array. SATA DVD-RW Drive; Monitor: Diagonal - 23.8 inches Aspect ratio - 16: 9 Resolution - not less than 1920 x 1080 Pixel size - no more than 0.278 mm			•		
least 6 and the number USB 3.0 interfaces is at least 2, installed with D-Sub, HDMI video outputs, the integrated network controller must be of the Ethernet 10/100/1000 Mbps RJ 45 port type, expansion slots must meet the requirements for the functioning of the video capture, video recording and audio recording system; Processor x86 Intel Core i7 (or equivalent), four physical cores, at least 3.5 GHz, cache at least 8 MB; The type of random access memory (RAM) must be at least 16 GB, and a two-channel operating mode must be organized. The storage drive must be in the form of at least two hard drives, each with a volume of at least 3000 GB, equipped with a SATA interface, with a spindle speed of at least 7200 rpm. Hard drives must be combined into a mirror array. SATA DVD-RW Drive; Monitor: Diagonal - 23.8 inches Aspect ratio - 16: 9 Resolution - not less than 1920 x 1080 Pixel size - no more than 0.278 mm			· ·		
Is at least 2, installed with D-Sub, HDMI video outputs, the integrated network controller must be of the Ethernet 10/100/1000 Mbps RI 45 port type, expansion slots must meet the requirements for the functioning of the video capture, video recording and audio recording system; Processor x86 Intel Core i7 (or equivalent), four physical cores, at least 3.5 GHz, cache at least 8 MB; The type of random access memory (RAM) must be at least 16 GB, and a two-channel operating mode must be organized. The storage drive must be in the form of at least two hard drives, each with a volume of at least 3000 GB, equipped with a SATA interface, with a spindle speed of at least 7200 rpm. Hard drives must be combined into a mirror array. SATA DVD-RW Drive; Monitor: Diagonal - 23.8 inches Aspect ratio - 16: 9 Resolution - not less than 1920 x 1080 Pixel size - no more than 0.278 mm					
Video outputs, the integrated network controller must be of the Ethernet 10/100/1000 Mbps RJ 45 port type, expansion slots must meet the requirements for the functioning of the video capture, video recording and audio recording system; Processor x86 Intel Core i7 (or equivalent), four physical cores, at least 3.5 GHz, cache at least 8 MB; The type of random access memory (RAM) must be at least DDR4 2400 SDRAM, the total size of RAM must be at least 16 GB, and a two-channel operating mode must be organized. The storage drive must be in the form of at least two hard drives, each with a volume of at least 3000 GB, equipped with a SATA interface, with a spindle speed of at least 7200 rpm. Hard drives must be combined into a mirror array. SATA DVD-RW Drive; Monitor: Diagonal - 23.8 inches Aspect ratio - 16: 9 Resolution - not less than 1920 x 1080 Pixel size - no more than 0.278 mm					
Personal Computer (Recording Station as a unit) Personal Computer (Recording Station as a unit) Processor x86 Intel Core i7 (or equivalent), four physical cores, at least 3.5 GHz, cache at least 8 MB; The type of random access memory (RAM) must be at least 10 GB, and a two-channel operating mode must be organized. The storage drive must be in the form of at least two hard drives, each with a volume of at least 3000 GB, equipped with a SATA interface, with a spindle speed of at least 7200 rpm. Hard drives must be combined into a mirror array. SATA DVD-RW Drive; Monitor: Diagonal - 23.8 inches Aspect ratio - 16: 9 Resolution - not less than 1920 x 1080 Pixel size - no more than 0.278 mm					
Personal Computer (Recording Station as a unit) Personal Computer (Recording Station as a unit) Personal Computer (Recording Station as a unit) Processor x86 Intel Core i7 (or equivalent), four physical cores, at least 3.5 GHz, cache at least 8 MB; The type of random access memory (RAM) must be at least DDR4 2400 SDRAM, the total size of RAM must be at least 16 GB, and a two-channel operating mode must be organized. The storage drive must be in the form of at least two hard drives, each with a volume of at least 3000 GB, equipped with a SATA interface, with a spindle speed of at least 7200 rpm. Hard drives must be combined into a mirror array. SATA DVD-RW Drive; Monitor: Diagonal - 23.8 inches Aspect ratio - 16: 9 Resolution - not less than 1920 x 1080 Pixel size - no more than 0.278 mm					
Personal Computer (Recording Station as a unit) Personal Computer (Recording Station as a unit) Processor x86 Intel Core i7 (or equivalent), four physical cores, at least 3.5 GHz, cache at least 8 MB; The type of random access memory (RAM) must be at least DDR4 2400 SDRAM, the total size of RAM must be at least 16 GB, and a two-channel operating mode must be organized. The storage drive must be in the form of at least two hard drives, each with a volume of at least 3000 GB, equipped with a SATA interface, with a spindle speed of at least 7200 rpm. Hard drives must be combined into a mirror array. SATA DVD-RW Drive; Monitor: Diagonal - 23.8 inches Aspect ratio - 16: 9 Resolution - not less than 1920 x 1080 Pixel size - no more than 0.278 mm					
Personal Computer (Recording Station as a unit) Porcessor x86 Intel Core i7 (or equivalent), four physical cores, at least 3.5 GHz, cache at least 8 MB; The type of random access memory (RAM) must be at least DDR4 2400 SDRAM, the total size of RAM must be at least 16 GB, and a two-channel operating mode must be organized. The storage drive must be in the form of at least two hard drives, each with a volume of at least 3000 GB, equipped with a SATA interface, with a spindle speed of at least 7200 rpm. Hard drives must be combined into a mirror array. SATA DVD-RW Drive; Monitor: Diagonal - 23.8 inches Aspect ratio - 16: 9 Resolution - not less than 1920 x 1080 Pixel size - no more than 0.278 mm					
Lot (Recording Station as a unit) **Processor x86 Intel Core i7 (or equivalent), four physical cores, at least 3.5 GHz, cache at least 8 MB; **The type of random access memory (RAM) must be at least DDR4 2400 SDRAM, the total size of RAM must be at least 16 GB, and a two-channel operating mode must be organized. **The storage drive must be in the form of at least two hard drives, each with a volume of at least 3000 GB, equipped with a SATA interface, with a spindle speed of at least 7200 rpm. Hard drives must be combined into a mirror array. **SATA DVD-RW Drive;**Monitor:** **Diagonal - 23.8 inches** **Aspect ratio - 16: 9** **Resolution - not less than 1920 x 1080* **Pixel size - no more than 0.278 mm*			•		
(Recording Station as a unit) Processor x86 Intel Core i7 (or equivalent), four physical cores, at least 3.5 GHz, cache at least 8 MB; The type of random access memory (RAM) must be at least DDR4 2400 SDRAM, the total size of RAM must be at least 16 GB, and a two-channel operating mode must be organized. The storage drive must be in the form of at least two hard drives, each with a volume of at least 3000 GB, equipped with a SATA interface, with a spindle speed of at least 7200 rpm. Hard drives must be combined into a mirror array. SATA DVD-RW Drive; Monitor: Diagonal - 23.8 inches Aspect ratio - 16: 9 Resolution - not less than 1920 x 1080 Pixel size - no more than 0.278 mm			video capture, video recording and audio		
Station as a unit) Processor x86 Intel Core 17 (or equivalent), four physical cores, at least 3.5 GHz, cache at least 8 MB; The type of random access memory (RAM) must be at least DDR4 2400 SDRAM, the total size of RAM must be at least 16 GB, and a two-channel operating mode must be organized. The storage drive must be in the form of at least two hard drives, each with a volume of at least 3000 GB, equipped with a SATA interface, with a spindle speed of at least 7200 rpm. Hard drives must be combined into a mirror array. SATA DVD-RW Drive; Monitor: Diagonal - 23.8 inches Aspect ratio - 16: 9 Resolution - not less than 1920 x 1080 Pixel size - no more than 0.278 mm		· -	recording system;	UNIT	2
at least 8 MB; The type of random access memory (RAM) must be at least DDR4 2400 SDRAM, the total size of RAM must be at least 16 GB, and a two-channel operating mode must be organized. The storage drive must be in the form of at least two hard drives, each with a volume of at least 3000 GB, equipped with a SATA interface, with a spindle speed of at least 7200 rpm. Hard drives must be combined into a mirror array. SATA DVD-RW Drive; Monitor: Diagonal - 23.8 inches Aspect ratio - 16: 9 Resolution - not less than 1920 x 1080 Pixel size - no more than 0.278 mm	10	-	I		
 The type of random access memory (RAM) must be at least DDR4 2400 SDRAM, the total size of RAM must be at least 16 GB, and a two-channel operating mode must be organized. The storage drive must be in the form of at least two hard drives, each with a volume of at least 3000 GB, equipped with a SATA interface, with a spindle speed of at least 7200 rpm. Hard drives must be combined into a mirror array. SATA DVD-RW Drive; Monitor: Diagonal - 23.8 inches Aspect ratio - 16: 9 Resolution - not less than 1920 x 1080 Pixel size - no more than 0.278 mm 					
must be at least DDR4 2400 SDRAM, the total size of RAM must be at least 16 GB, and a two-channel operating mode must be organized. • The storage drive must be in the form of at least two hard drives, each with a volume of at least 3000 GB, equipped with a SATA interface, with a spindle speed of at least 7200 rpm. Hard drives must be combined into a mirror array. • SATA DVD-RW Drive; Monitor: • Diagonal - 23.8 inches • Aspect ratio - 16: 9 • Resolution - not less than 1920 x 1080 • Pixel size - no more than 0.278 mm			l ·		
total size of RAM must be at least 16 GB, and a two-channel operating mode must be organized. • The storage drive must be in the form of at least two hard drives, each with a volume of at least 3000 GB, equipped with a SATA interface, with a spindle speed of at least 7200 rpm. Hard drives must be combined into a mirror array. • SATA DVD-RW Drive; Monitor: • Diagonal - 23.8 inches • Aspect ratio - 16: 9 • Resolution - not less than 1920 x 1080 • Pixel size - no more than 0.278 mm					
and a two-channel operating mode must be organized. The storage drive must be in the form of at least two hard drives, each with a volume of at least 3000 GB, equipped with a SATA interface, with a spindle speed of at least 7200 rpm. Hard drives must be combined into a mirror array. SATA DVD-RW Drive; Monitor: Diagonal - 23.8 inches Aspect ratio - 16: 9 Resolution - not less than 1920 x 1080 Pixel size - no more than 0.278 mm					
be organized. The storage drive must be in the form of at least two hard drives, each with a volume of at least 3000 GB, equipped with a SATA interface, with a spindle speed of at least 7200 rpm. Hard drives must be combined into a mirror array. SATA DVD-RW Drive; Monitor: Diagonal - 23.8 inches Aspect ratio - 16: 9 Resolution - not less than 1920 x 1080 Pixel size - no more than 0.278 mm			-		
 The storage drive must be in the form of at least two hard drives, each with a volume of at least 3000 GB, equipped with a SATA interface, with a spindle speed of at least 7200 rpm. Hard drives must be combined into a mirror array. SATA DVD-RW Drive; Monitor: Diagonal - 23.8 inches Aspect ratio - 16: 9 Resolution - not less than 1920 x 1080 Pixel size - no more than 0.278 mm 					
least two hard drives, each with a volume of at least 3000 GB, equipped with a SATA interface, with a spindle speed of at least 7200 rpm. Hard drives must be combined into a mirror array. SATA DVD-RW Drive; Monitor: Diagonal - 23.8 inches Aspect ratio - 16: 9 Resolution - not less than 1920 x 1080 Pixel size - no more than 0.278 mm					
interface, with a spindle speed of at least 7200 rpm. Hard drives must be combined into a mirror array. • SATA DVD-RW Drive; Monitor: • Diagonal - 23.8 inches • Aspect ratio - 16: 9 • Resolution - not less than 1920 x 1080 • Pixel size - no more than 0.278 mm					
7200 rpm. Hard drives must be combined into a mirror array. SATA DVD-RW Drive; Monitor: Diagonal - 23.8 inches Aspect ratio - 16: 9 Resolution - not less than 1920 x 1080 Pixel size - no more than 0.278 mm			of at least 3000 GB, equipped with a SATA		
into a mirror array. SATA DVD-RW Drive; Monitor: Diagonal - 23.8 inches Aspect ratio - 16: 9 Resolution - not less than 1920 x 1080 Pixel size - no more than 0.278 mm			interface, with a spindle speed of at least		
 SATA DVD-RW Drive; Monitor: Diagonal - 23.8 inches Aspect ratio - 16: 9 Resolution - not less than 1920 x 1080 Pixel size - no more than 0.278 mm 			7200 rpm. Hard drives must be combined		
 Monitor: Diagonal - 23.8 inches Aspect ratio - 16: 9 Resolution - not less than 1920 x 1080 Pixel size - no more than 0.278 mm 			•		
 Diagonal - 23.8 inches Aspect ratio - 16: 9 Resolution - not less than 1920 x 1080 Pixel size - no more than 0.278 mm 			ŕ		
 Aspect ratio - 16: 9 Resolution - not less than 1920 x 1080 Pixel size - no more than 0.278 mm 					
 Resolution - not less than 1920 x 1080 Pixel size - no more than 0.278 mm 					
Pixel size - no more than 0.278 mm			I		
■ Digitaless - Hot less than 250 ta / III .			_		
Contrast - not less than 1,000M: 1			_		
Viewing angles - not less than 178 °			·		
horizontally, 178 ° vertically					



- Response time no more than 5 ms
- The presence of LED backlight
- The number of colors is at least 16.7 million.
- The surface of the monitor must be nonreflective and antistatic
- The presence of connectors at least 2, D-Sub, HDMI
- Black color.

Input Devices:

- Keyboard and mouse set, wired with USB connection interface, packed in one package
- With support for the Russian language at least 102 keys
- Optical mouse
- Device color black

Operating system:

- Type: license
- Version: Windows 10 Pro Rus
- Bit depth: 64x
- License type: DSP OEI

Software:

- Name: Microsoft Office Home and Business
 - Version: 2016 Type: license
- Localization: Russian
- License term: unlimited
- Product type: full boxed license (FPP, BOX)

Headphones:

- Device type: headphones
- Style: full-size, closed
- Type: dynamic
- Frequency response range: 14 20,000 Hz
- Sensitivity: 112 dBImpedance: 32 Ohm
- Harmonic Distortion: 0.5%
- Mount type: headband
- Cable connection: one-way
- Headphone jack: mini jack 3.5 mm
- Headphone connector shape: straight
- 6.3 mm adapter included
- Gold plated connectors
- Cable length: 3m

Network filter:



Lots	Item Name	Specification	Unit measure	Quantity
		 Auto fuse, short circuit and overload protection, overheating protection, overvoltage protection Load current: not less than 10 A Operating voltage: 220-240V Plastic type: shockproof non-flammable ABS The number of output sockets: not less than 6 pcs. Cord length: not less than 3 m 		
Lot 11	Motherboard	 LGA1151 compatible or equivalent 4 DIMM slots for DDR4 RAM modules, maximum supported system memory up to 64GB Compatible with DDR4 2666/2400/2133 MHz RAM modules The number of USB 2.0 interfaces shall be at least 6 and USB 3.0 interfaces shall be at least 2, with installed video outputs D-Sub, HDMI, the integrated network controller must be of the Ethernet 10/100/1000 Mbit/s type with an RJ 45 port At least 1 PCI Express x16 port At least 2 PCI Express x1 slots At least 6 SATA 6Gb/s connectors 	UNIT	5
Lot 12	Random access memory (RAM)	DDR4, at least 8 Gigabytes	UNIT	15
Lot 13	Monitor	 Diagonal - 23.8 inches Aspect ratio - 16: 9 Resolution - not less than 1920 x 1080 Pixel size - no more than 0.278 mm Brightness - not less than 250 cd /m². Contrast - not less than 1,000M: 1 Viewing angles - not less than 178 ° horizontally, 178 ° vertically Response time - no more than 5 ms The presence of LED backlight The number of colors is at least 16.7 million. The surface of the monitor must be non-reflective and antistatic The presence of connectors - at least 2, D-Sub, HDMI Black color. 	UNIT	5



Lots	Item Name	Specification	Unit	Quantity
LOCS	rtem rtame	Specification	measure	Qualitity
		 Standard not lower than HDMI 1.4 		
Lot	HDMI cable 1.5m	 HDMI Male to HDMI Male 	UNIT	20
14	TIDIVII CUDIC 1.5III	 Length not less than 1.5 m 	OWN	20
		 Total cross section: not less than 28 AWG 		
		 Standard not lower than HDMI 1.4 		
Lot	HDMI cable 3m	 HDMI Male to HDMI Male 	UNIT	20
15	HDIVII Cable 3III	 Length not less than 3 m 	ONIT	20
		 Total cross section: not less than 24 AWG 		
		 Standard not lower than HDMI 1.4 		
Lot	HDMI cable 10m	 HDMI Male to HDMI Male 	UNIT	20
16	HDIVII Cable 10111	 Length not less than 10 m 	ONIT	20
		 Total cross section: not less than 24 AWG 		
		 Standard not lower than HDMI 1.4 		
Lot	Lot 17 HDMI cable 20m	 HDMI Male to HDMI Male 	UNIT	20
17		 Length not less than 20 m 	UNIT	20
		 Total cross section: not less than 22 AWG 		



ANNEX C SUPPLIER'S QUOTATION

(This Form must be submitted using the Supplier's Official Letterhead/Stationery in the format specified below)

We, the undersigned, hereby accept the IDLO's General Terms and Conditions in full and Payment Policy of payment within 30 days after delivery of service on presentation of complete and correct invoice. We hereby offer to supply the items listed below in conformity with the specification and requirements of IDLO as per RFQ N_571-KGZ_21

Company Name	
Company Full Address	
Date	
Signature	
Stamp	
Contact Person	
Telephone number	
Email address	



Table 1: Offer to Supply Goods / Services Compliant with Technical Specifications and Requirements

		□ Comply	10	Unit	IP camera	Lot 6
		☐ Comply☐ Not Comply. Alternative specification offered (please attach)	10	Unit	4 TB hard drive	Lot 5
		☐ Comply☐ Not Comply. Alternative specification offered (please attach)	2	Unit	Network video recorder (NVR)	Lot 4
		☐ Comply☐ Not Comply. Alternative specification offered (please attach)	10	Unit	Video conferencing subsystem image display screen	Lot 3
		☐ Comply☐ Not Comply. Alternative specification offered (please attach)	10	Unit	3 TB hard drive	Lot 2
		□ Comply □ Not Comply. Alternative specification offered (please attach)	15	Unit	Uninterruptible Power Supply for Personal Computer	Lot 1
Total amount in KGS	Unit rate in KGS	Compliance with Technical Specifications in Annex B	Quantity	Unit measure	ltem	Lots

	□ Comply	5	Unit	Monitor	Lot 13
	☐ Comply☐ Not Comply. Alternative specification offered (please attach)	15	Unit	Random access memory (RAM)	Lot 12
	☐ Comply☐ Not Comply. Alternative specification offered (please attach)	ر. ت	Unit	Motherboard	Lot 11
	☐ Comply☐ Not Comply. Alternative specification offered (please attach)	2	Unit	Personal Computer (Recording Station as a unit)	Lot 10
	☐ Comply☐ Not Comply. Alternative specification offered (please attach)	5	Unit	Video capture card	Lot 9
	☐ Comply☐ Not Comply. Alternative specification offered (please attach)	30	Unit	PC power supply	Lot 8
	☐ Comply☐ Not Comply. Alternative specification offered (please attach)	5	Unit	PoE switch	Lot 7
	☐ Not Comply. Alternative specification offered (please attach)				

	ing taxes	Total amount including taxes	Total a		
	ble)	Taxes (if applicable)	Та		
		Sub-total			
	□ Comply□ Not Comply. Alternative specification offered (please attach)	20	Unit	HDMI cable 20m	Lot 17
	□ Comply□ Not Comply. Alternativespecification offered (please attach)	20	Unit	HDMI cable 10m	Lot 16
	□ Comply□ Not Comply. Alternative specification offered (please attach)	20	Unit	HDMI cable 3m	Lot 15
	□ Comply□ Not Comply. Alternativespecification offered (please attach)	20	Unit	HDMI cable 1.5m	Lot 14
	☐ Not Comply. Alternative specification offered (please attach)				

Table 2: Offer for After-Sale Services and Other Conditions

Other Information		Responses	ses
	Yes, we will comply	No, we cannot comply	If you cannot comply, pls. indicate counter proposal
Warranty: Minimum one (1) year warranty on both parts and labour from Lot 1 to Lot 13			
Delivery on basis of Incoterms Delivery Duty Paid (DDP) at 171 Junusalieva Street, Bishkek, Kyrgyzstan			
Goods will be delivered within 90 days after receipt of PO or contract from IDLO			

ANNEX D ANNEX D AND AND AND IDLO SUPPLIER CODE OF CONDUCT

Any quote submission will imply the unconditional acceptance of IDLO General Terms and Conditions for Goods and Services and adherence to the Supplier Code of Conduct.

The documents are available on IDLO Procurement Website:

https://www.idlo.int/sites/default/files/documents/general terms and conditions for goods august 2020.pdf

https://www.idlo.int/sites/default/files/documents/general terms and conditions for services august 2020.pdf

https://www.idlo.int/sites/default/files/documents/idlo-supplier-code-of-conduct.pdf